



# Test Report : DCW08W8-12

---

8W DIP Package 8:1 Ultra-Wide Input DC-DC Regulated Converter

## ■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

## ■ SAFETY TEST

Safety test

## ■ RELIABILITY TEST

Environment Test

## DESIGN VERIFY TEST

### OUTPUT FUNCTION TEST

| NO | TEST ITEM        | SPECICATION   | TEST CONDITION                                | RESULT                                     | VERDICT |
|----|------------------|---------------|-----------------------------------------------|--------------------------------------------|---------|
| 1  | VOLTAGE ACCURACY | -2.0% ~ +2.0% | I/P:24VDC<br>O/P:FULL LOAD<br>Ta:25°C         | V1: -0.32%<br>V2: -0.36%                   | P       |
| 2  | RIPPLE & NOISE   | 100 mVp-p     | I/P:24VDC<br>O/P:FULL LOAD<br>Ta:25°C         | V1: 7 mV<br>V2: 7 mV                       | P       |
| 3  | LINE REGULATION  | -0.5% ~ +0.5% | I/P:9VDC~75VDC<br>O/P:FULL LOAD<br>Ta:25°C    | V1: +0.00% ~ -0.04%<br>V2: -0.04% ~ -0.03% | P       |
| 4  | LOAD REGULATION  | -0.5% ~ +0.5% | I/P:24VDC<br>O/P:0% LOAD~FULL LOAD<br>Ta:25°C | V1: +0.00% ~ +0.05%<br>V2: -0.01% ~ -0.03% | P       |
| 5  | CROSS REGULATION | -5% ~ +5.0%   | I/P:24VDC<br>O/P:25%~FULL LOAD<br>Ta:25°C     | V1: +0.39%<br>V2: +0.59%                   | P       |

### INPUT FUNCTION TEST

| NO | TEST ITEM  | SPECICATION                           | TEST CONDITION                             | RESULT                                   | VERDICT |
|----|------------|---------------------------------------|--------------------------------------------|------------------------------------------|---------|
| 1  | EFFICIENCY | 86%                                   | I/P:24VDC<br>O/P:FULL LOAD<br>Ta:25°C      | 87.10%                                   | P       |
| 2  | DC CURRENT | 383 mA / FULL LOAD<br>10 mA / NO LOAD | I/P:24VDC<br>O/P:NO / FULL LOAD<br>Ta:25°C | 379.9 mA / FULL LOAD<br>7.9 mA / NO LOAD | P       |

### PROTECTION FUNCTION TEST

| NO | TEST ITEM               | SPECICATION                                  | TEST CONDITION                          | RESULT                                  | VERDICT |
|----|-------------------------|----------------------------------------------|-----------------------------------------|-----------------------------------------|---------|
| 1  | SHORT PROTECTION        | CONTINUOUS                                   | I/P:75VDC<br>O/P:FULL LOAD<br>Ta:25°C   | CONTINUOUS,<br>AUTOMATIC RECOVERY       | P       |
| 2  | OVER LOAD PROTECTION    | 200~300%                                     | I/P:24VDC<br>O/P:TESTING<br>Ta:25°C     | 286.8%<br>HICCUP MODE<br>AUTO-RECOVER   | P       |
| 3  | CASE TEMPERATURE        | +110°C max                                   | I/P:24VDC<br>O/P:TESTING<br>Ta: TESTING | OK<br>AUTOMATIC RECOVERY                | P       |
| 4  | OVER VOLTAGE PROTECTION | YES                                          | I/P: 24VDC<br>O/P: MIN LOAD<br>Ta:25°C  | PROTECTION TYPE :<br>CLAMP BY TVS DIODE | P       |
| 5  | UNDER VOLTAGE LOCKOUT   | START-UP 8.8V<br>SHUTDOWN OLTA GE 8.0V(Type) | I/P:TESTING<br>O/P:FULL LOAD<br>Ta:25°C | 8.59 VDC<br>8.07 VDC                    | P       |

## SAFETY TEST

### SAFETY TEST

| NO | TEST ITEM            | SPECIFICATION         | TEST CONDITION                  | RESULT                        | VERDICT |
|----|----------------------|-----------------------|---------------------------------|-------------------------------|---------|
| 1  | WITHSTAND VOLTAGE    | I/P-O/P:3000 VDC/min  | I/P-O/P:3000 VDC/min<br>Ta:25°C | I/P-O/P: 0.002mA<br>NO DAMAGE | P       |
| 2  | ISOLATION RESISTANCE | I/P-O/P:500VDC>1000MΩ | I/P-O/P:500 VDC<br>Ta:25°C      | I/P-O/P>1000MΩ<br>NO DAMAGE   | P       |

## RELIABILITY TEST

### ENVIRONMENT TEST

| NO | TEST ITEM                    | SPECIFICATION                                                                                                                                                                                              | TEST CONDITION                                                                                                                                                                                                      | RESULT    |          |   |   |   |   |      |        |         |         |  |
|----|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|----------|---|---|---|---|------|--------|---------|---------|--|
| 1  | TEMPERATURE RISE TEST        | 1. ROOM AMBIENT BURN-IN : 4HRS<br>I/P:24VDC O/P:FULL LOAD Ta=25°C<br>2. HIGH AMBIENT BURN-IN : 4HRS<br>I/P:24VDC O/P:FULL LOAD Ta=80°C<br>3. HIGH AMBIENT BURN-IN : 4HRS<br>I/P:24VDC O/P:50% LOAD Ta=90°C | <table border="1"> <thead> <tr> <th>NO</th><th>Position</th><th>1</th><th>2</th><th>3</th></tr> </thead> <tbody> <tr> <td>1</td><td>CASE</td><td>52.5°C</td><td>101.9°C</td><td>105.4°C</td></tr> </tbody> </table> | NO        | Position | 1 | 2 | 3 | 1 | CASE | 52.5°C | 101.9°C | 105.4°C |  |
| NO | Position                     | 1                                                                                                                                                                                                          | 2                                                                                                                                                                                                                   | 3         |          |   |   |   |   |      |        |         |         |  |
| 1  | CASE                         | 52.5°C                                                                                                                                                                                                     | 101.9°C                                                                                                                                                                                                             | 105.4°C   |          |   |   |   |   |      |        |         |         |  |
| 2  | LOW TEMPERATURE TURN ON TEST | TURN ON AFTER 4 HOURS                                                                                                                                                                                      | I/P:24VDC<br>O/P: FULL LOAD<br>Ta= -40°C                                                                                                                                                                            | TEST : OK |          |   |   |   |   |      |        |         |         |  |

### OTHER

| NO | TEST ITEM | SPECIFICATION                                                            | TEST CONDITION | RESULT |
|----|-----------|--------------------------------------------------------------------------|----------------|--------|
| 1  | MTBF      | MIL-HDBK-217F,GB,25°C<br>TOTAL FAILURE RATE : 3.333<br>M.T.B.F : 300KHRS |                |        |

| TEST RESULT | TESTER       | APPROVAL    |
|-------------|--------------|-------------|
| PASS        | ARCHEN HSIAO | PETER CHENG |